



CHG: D areas

RNAV STAR RWY 07

ARLOM 1E NAXEP 1E OTKAP 1E VEHUF 1E

DME/DME OPS:	NOT SUPPORTED	RCF:	SELECT TRANSPONDER CODE 7600
ROUTES:	RNAV PROC CODING ON THE VERSO OF THE CHART ATC WILL GIVE DESCENT CLEARANCES	RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED: FOLLOW THE STAR TO THE RESPECTIVE RWY AND EXECUTE IAP AND LAND	
WPT CONSTRAINTS:	ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC	DURING RADAR VECTORING BEFORE IAF: IN ACCORDANCE WITH THE RULES OF THE AIR	
CD OPS:	BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR	AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3	
NOISE ABATEMENT:	AVOID OVERFLYING THE CITY OF KOUVOLA BELOW 2000		

EFUT RNAV STAR RWY 07										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Constraints		
			ID	Flyover				LVL	LVL	Speed
ARLOM 1E RNAV 1	010	IF	ARLOM	-	-	-	-	F100+		
	020	TF	ELSUW	-	264°	274.2°T	22.3			
	030	TF	ATVAP	-	248°	258.1°T	10.5	A2300+		K240-
	040	TF	ULNAV	-	338°	347.8°T	5.0	A2300+		

NAXEP 1E RNAV 1	010	IF	NAXEP	-	-	-	-	F100+		
	020	TF	SUZCU	-	177°	186.9°T	3.5	A2300+		K240-
	030	TF	ULNAV	-	147°	157.0°T	4.5	A2300+		

OTKAP 1E RNAV 1	010	IF	OTKAP	-	-	-	-	F100+		
	020	TF	EPATU	-	219°	229.5°T	6.4			
	030	TF	POWUQ	-	248°	258.3°T	9.6			
	040	TF	USIMI	-	248°	258.0°T	10.5	A2300+		K240-
	050	TF	ULNAV	-	157°	167.7°T	5.0	A2300+		

VEHUF 1E RNAV 1	010	IF	VEHUF	-	-	-	-	F100+		
	020	TF	ULNAV	-	059°	069.0°T	15.2	A2300+		

RNAV Holdings							
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM
ULNAV	347.8°T	338°	Right	K230-	A2300	1 MIN	-

WPT COORD
SEE PAGE EFUT AD 2.15 - 1