



RNAV STAR RWY 08

ARBEV 1B ATSEN 1B ERTOP 1B USUPO 1B

DME/DME OPS: NOT SUPPORTED

RCF: SELECT TRANSPONDER CODE 7600

ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART
ATC WILL GIVE DESCENT CLEARANCES

RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED:
FOLLOW THE STAR TO THE RESPECTIVE RWY
AND EXECUTE IAP AND LAND

WPT CONSTRAINTS: ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS
PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC

AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

CD OPS: BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR

CHG: new PROC

EFHA RNAV STAR RWY 08										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
ARBEV 1B RNAV 1	010	IF	ARBEV	-	-	-	-		F100+	
	020	TF	DOMMU	-	336°	346.0°T	8.3		A2700+	K240-
	030	TF	TIPUB	-	346°	355.8°T	5.0		A2700+	

ATSEN 1B RNAV 1	010	IF	ATSEN	-	-	-	-		F100+	
	020	TF	BOZUS	-	241°	251.2°T	27.5	L	A2700+	K240-
	030	TF	TIPUB	-	166°	175.8°T	5.0		A2700+	

ERTOP 1B RNAV 1	010	IF	ERTOP	-	-	-	-		F100+	
	020	TF	BOZUS	-	249°	258.7°T	29.7	L	A2700+	K240-
	030	TF	TIPUB	-	166°	175.8°T	5.0		A2700+	

USUPO 1B RNAV 1	010	IF	USUPO	-	-	-	-		F100+	
	020	TF	DOMMU	-	288°	298.1°T	19.1	R	A2700+	K240-
	030	TF	TIPUB	-	346°	355.8°T	5.0		A2700+	

RNAV Holdings								
ID	INBD TR	INBD MAG	Turn Direction	MAX IAS	MNM HLDG LVL	TIME	DIST NM	
TIPUB	176.4°T	167°	Right	230 KT	A2700	1 MIN	-	

WPT COORD
SEE PAGE EFHA AD 2.15 - 1