



RNAV STAR RWY 26

ARBEV 1A ATSEN 1A ERTOP 1A USUPO 1A

DME/DME OPS: NOT SUPPORTED

RCF: SELECT TRANSPONDER CODE 7600

ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART  
ATC WILL GIVE DESCENT CLEARANCES

RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED:  
FOLLOW THE STAR TO THE RESPECTIVE RWY  
AND EXECUTE IAP AND LAND

WPT CONSTRAINTS: ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS  
PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC

AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

CD OPS: BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR

CHG: new PROC

EFHA RNAV STAR RWY 26										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
ARBEV 1A RNAV 1	010	IF	ARBEV	-	-	-	-		F100+	
	020	TF	SISVU	-	055°	064.4°T	22.3	L	A2700+	K240-
	030	TF	MITKU	-	347°	356.5°T	5.0		A2700+	

ATSEN 1A RNAV 1	010	IF	ATSEN	-	-	-	-		F100+	
	020	TF	NAKUP	-	198°	207.4°T	8.5	L	A2700+	K240-
	030	TF	MITKU	-	167°	176.4°T	5.0		A2700+	

ERTOP 1A RNAV 1	010	IF	ERTOP	-	-	-	-		F100+	
	020	TF	MITKU	-	205°	215.2°T	11.7		A2700+	

USUPO 1A RNAV 1	010	IF	USUPO	-	-	-	-		F100+	
	020	TF	SISVU	-	017°	026.8°T	11.7	L	A2700+	K240-
	030	TF	MITKU	-	347°	356.5°T	5.0		A2700+	

RNAV Holdings								
ID	INBD TR	INBD MAG	Turn Direction	MAX IAS	MNM HLDG LVL	TIME	DIST NM	
MITKU	356.5°T	347°	Left	230 KT	A2700	1 MIN	-	

WPT COORD
SEE PAGE EFHA AD 2.15 - 1