



CHG: PBN. ADDN R78A, R78B, R121. DEL R78

RNAV SID RWY 04L

ADIVO 3Z KOIVU 3Z KUVEM 3Z NEPEK 3Z NUNTO 3Z RENKU 3Z TEVRU 3Z VALOX 3Z

- | | | | |
|-------------------|---|------------------|--|
| DME/DME OPS: | NOT SUPPORTED | CLIMB ALTITUDE: | CLIMB TO 4000 FT OR ASSIGNED ALTITUDE IF LOWER.
CLIMB TO A HIGHER LEVEL ONLY WHEN CLEARED BY ATC. |
| ROUTES: | RNAV PROC CODING ON THE VERSO OF THE CHART | RADIO CONTACT: | MAINTAIN TWR FREQ UNTIL 1500 FT, THEN CONTACT
HELSINKI RADAR FREQ 129.850. |
| SQUAWK: | WHEN LINING UP SQUAWK THE ASSIGNED CODE | NOISE ABATEMENT: | AFTER TAKE-OFF CLIMB AS RAPIDLY AS PRACTICABLE
TO AT LEAST 2000 FT ABOVE AD ELEV. |
| ADDITIONS TO SID: | INSTRUCTIONS CONTAINING DEVIATIONS FROM THE SID
(TEMPORARY ALTITUDE RESTRICTIONS ETC) MAY BE
INCLUDED IN THE ATC CLEARANCE PRIOR TO TAKE-OFF. | AREA MNM ALT: | SEE AMA INDEX, AIP ENR 6.1 - 3 |
| INITIAL CLIMB: | MNM TURNING ALTITUDE ACCORDING TO RTE CODING.
PDG 5.0 % (304 FT/NM) UNTIL 4000 FT BASED ON
AIRSPACE RESTRICTIONS. | | |

EFHK RNAV SID RWY 04L										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
ADIVO 3Z RNAV 1	010	CA	-	-	038°	047.3°T	-	L	A680+	
	020	DF	HK903	-	-	-	-			K230-
	030	TF	HK908	-	277°	286.0°T	6.2	L		K250-
	040	TF	ADIVO	-	241°	250.5°T	24.2			
KOIVU 3Z RNAV 1	010	CA	-	-	038°	047.3°T	-	L	A680+	
	020	DF	HK903	-	-	-	-			K230-
	030	TF	HK908	-	277°	286.0°T	6.2	L		K250-
	040	TF	HK909	-	190°	198.9°T	6.0		A4000+	
	050	TF	KOIVU	-	172°	180.9°T	29.8			
KUVEM 3Z RNAV 1	010	CA	-	-	038°	047.3°T	-	L	A680+	
	020	DF	HK903	-	-	-	-			K230-
	030	TF	HK908	-	277°	286.0°T	6.2	L		K250-
	040	TF	KUVEM	-	230°	239.1°T	28.3			
NEPEK 3Z RNAV 1	010	CA	-	-	038°	047.3°T	-	L	A680+	
	020	DF	HK903	-	-	-	-			K230-
	030	TF	NEPEK	-	317°	326.2°T	24.4			
NUNTO 3Z RNAV 1	010	CA	-	-	038°	047.3°T	-	L	A680+	
	020	DF	HK903	-	-	-	-			K230-
	030	TF	HK908	-	277°	286.0°T	6.2	L		K250-
	040	TF	NUNTO	-	221°	230.7°T	33.1			
RENKU 3Z RNAV 1	010	CA	-	-	038°	047.3°T	-	L	A680+	
	020	DF	HK903	-	-	-	-			K230-
	030	TF	HK908	-	277°	286.0°T	6.2	L		K250-
	040	TF	HK909	-	190°	198.9°T	6.0	L	A4000+	
	050	TF	RENKU	-	157°	166.6°T	28.1			
TEVRU 3Z RNAV 1	010	CA	-	-	038°	047.3°T	-	L	A680+	
	020	DF	HK903	-	-	-	-			K230-
	030	TF	TEVRU	-	343°	351.9°T	25.2			
VALOX 3Z RNAV 1	010	CA	-	-	038°	047.3°T	-	L	A680+	
	020	DF	HK903	-	-	-	-			K230-
	030	TF	HK908	-	277°	286.0°T	6.2	L		K250-
	040	TF	HK909	-	190°	198.9°T	6.0		A4000+	
	050	TF	VALOX	-	195°	204.3°T	40.1			

WPT COORD

SEE PAGE EFHK AD 2.15 - 1