



CHG: DEL D117, R117, ADDN R119A, R119B, D200

RNAV STAR RWY 04
LUSAG 1A NEKUX 1A SOTIT 1A

- NAV SPECIFICATION: RNAV 1 OR P-RNAV APPROVAL REQUIRED. OTHERWISE ADVISE ATC
 - DME/DME OPS: NOT SUPPORTED
 - ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART
ATC WILL GIVE DESCENT CLEARANCES
 - WPT CONSTRAINTS: ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC
 - CD OPS: BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR
 - RCF: SELECT TRANSPONDER CODE 7600
- RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED: FOLLOW THE STAR TO THE RESPECTIVE RWY AND EXECUTE IAP AND LAND

AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

EFIV RNAV STAR RWY 04										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
LUSAG 1A RNAV 1 or P-RNAV	010	IF	LUSAG	-	-	-	-		F100+	
	020	TF	KEPEX	-	050°	061.9°T	16.1		A3500+	
	-									

NEKUX 1A RNAV 1 or P-RNAV	010	IF	NEKUX	-	-	-	-		F100+	
	020	TF	LANRU	-	183°	195.6°T	10.6	R		
	030	TF	NUKMO	-	215°	227.2°T	12.8			
	040	TF	RUKEM	-	215°	226.8°T	11.5	L	A3500+	K240-
	050	TF	KEPEX	-	124°	136.5°T	5.0		A3500+	

SOTIT 1A RNAV 1 or P-RNAV	010	IF	SOTIT	-	-	-	-		F100+	
	020	TF	VENAB	-	343°	355.5°T	10.4	L	A3500+	K240-
	030	TF	KEPEX	-	304°	316.8°T	5.0		A3500+	

RNAV Holdings									
ID	INBD TR	INBD MAG	Turn Direction	MAX IAS	MNM HLDG LVL	TIME	DIST NM		
KEPEX	047.0°T	035°	Left	230 KT	A3500	1 MIN	-		

WPT COORD
SEE PAGE EFIV AD 2.15 - 1